

P28845.A10

**IN THE CLAIMS**

Please cancel claims 162-223 and 244 without prejudice or disclaimer. Applicant expressly reserves the right to file the subject matter of these claims in one or more divisional applications;

Please amend claims 224, 228, 230, 237, 259-263, 273 and 274; and

Please add new claims 275-289 as follows:

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

Claims 1-223 (Canceled).

224. (Currently Amended) A device for producing a tissue web comprising:  
at least one drying cylinder;  
a creping doctor arranged on the at least one drying cylinder;  
a winding device for winding up the tissue web;  
a transfer device at least largely bridging an entire distance between the creping doctor and the winding device and moves around a winding drum of the winding device; and  
a free web draw arranged between the creping doctor and the winding device,  
wherein the tissue web is supported on only one side by the transfer device, and  
wherein the winding device comprises a winding nip which produces a line force that is less than or equal to 0.8 kN/m.

225. (Previously Presented) The device of claim 224, wherein the free web draw is one of:  
< 1 m; and  
< 0.5 m.

226. (Previously Presented) The device of claim 224, wherein the transfer device is at least one of:  
arranged on an underside of the tissue web; and

{P28845 00768603.DOC}

3

P28845.A10

begins to support the tissue web underneath the creping doctor.

227. (Previously Presented) The device of claim 224, wherein the transfer device comprises one of:

- a belt;
- an embossing belt;
- a felt;
- an embossing felt;
- a membrane;
- a Spectra membrane;
- a structured material; and
- a TAD belt.

228. (Currently Amended) The device of claim 224, wherein the transfer device is led through ~~[[a]]~~ the winding nip of the winding device with the tissue web.

229. (Previously Presented) The device of claim 224, further comprising a device which subjects the tissue web to a patterning in a winding nip of the winding device.

230. (Currently Amended) The device of claim 224, wherein the ~~winding device comprises a winding nip generating a line force of~~ is about 0.2 kN/m.

231. (Previously Presented) The device of claim 224, further comprising one of:  
a device for subjecting the tissue web to wet formation arranged between the at least one drying cylinder and the winding device;

a device for rewetting and applying a vacuum to the tissue web arranged between the at least one drying cylinder and the winding device;

a device for rewetting and a device for applying a vacuum to the tissue web arranged between the at least one drying cylinder and the winding device;

{P28845 00768603.DOC}

P28845.A10

a device for rewetting and a device for applying a vacuum to the tissue web arranged between the at least one drying cylinder and the winding device, the rewetting device being arranged on an upper side of the tissue web and the device for applying vacuum being arranged on an underside of the tissue web; and

a device for rewetting, a device for applying a vacuum, and a device for drying the tissue web arranged between the at least one drying cylinder and the winding device, the drying device is arranged after the rewetting device and the device for applying a vacuum.

232. (Previously Presented) The device of claim 224, further comprising at least one of:  
at least one infrared drying device; and  
a drying hood.

233. (Previously Presented) The device of claim 224, wherein the tissue web has, at the creping doctor, one of:

a dryness of between about 70% and about 100%; and  
a dryness of between about 93% and about 98%.

234. (Previously Presented) The device of claim 224, wherein a creping rate is one of:  
between about 0% and about 50%; and  
between about 10% and about 25%.

235. (Previously Presented) The device of claim 224, wherein the device does not utilizes a threading system.

236. (Previously Presented) The device of claim 224, further comprising one of:  
a device for applying vacuum to the tissue web positioned after the creping doctor; and  
a device for blowing on the tissue web positioned after the creping doctor.

P28845.A10

237. (Currently Amended) The device of claim 224, wherein the winding device drum comprises one of:

- ~~a winding drum;~~
- an uncovered winding drum;
- a covered winding drum;
- a winding drum having a smooth shell;
- a winding drum having a blind-drilled shell;
- a winding drum having a drilled shell; and
- a winding drum having a shell with grooves.

238. (Previously Presented) The device of claim 224, further comprising one of:  
a pulper arranged under the at least one drying cylinder;  
a pulper arranged under the winding device; and  
a device for blowing off excess paper present on a winding drum of the winding device into a pulper.

239. (Previously Presented) The device of claim 224, further comprising one of:  
an air deflector arranged on a winding drum of the winding device; and  
a doctor arranged on a winding drum of the winding device.

240. (Previously Presented) The device of claim 224, wherein the tissue web has at least one of:

- a low basis weight; and
- a low tensile strength.

241. (Previously Presented) The device of claim 224, further comprising:  
a headbox;  
an endless carrier belt; and  
a press nip formed between the at least one drying cylinder and a backing unit.

{P28845 00768603.DOC}

P28845.A10

242. (Previously Presented) The device of claim 241, wherein the headbox comprises a multilayer headbox, to which at least two grades of stock can be supplied, and further comprising one of:

- a device for influence a hardness of a roll upon which the tissue web is wound;
- a device for controlling a hardness of a roll upon which the tissue web is wound; and
- a device for regulating a hardness of a roll upon which the tissue web is wound.

243. (Previously Presented) The device of claim 224, wherein the at least one drying cylinder is a Yankee cylinder.

Claim 244. (Canceled).

245. (Previously Presented) The device of claim 224, further comprising:

a former having two circulating endless belts which run together and form a stock inlet gap, the two circulating endless belts being led over a forming element such an inner belt of the two circulating endless belts comes into contact with the forming element.

246. (Previously Presented) The device of claim 224, further comprising a Crescent former and a felt for forming the tissue web.

247. (Previously Presented) The device of claim 224, wherein the tissue web is led through at least one shoe press on a carrier belt.

248. (Previously Presented) The device of claim 224, further comprising one of:

- a backing unit assigned to the at least one drying cylinder; and
- a shoe press unit arranged at the at least one drying cylinder.

249. (Previously Presented) The device of claim 224, further comprising a drying hood and a press nip arranged at the at least one drying cylinder.

{P28845 00768603.DOC}

P28845.A10

250. (Previously Presented) The device of claim 224, further comprising one of:

a multilayer headbox subdivided into at least two channels by at least one slat extending over an entire machine width;

a multilayer headbox subdivided at least substantially symmetrically into two channels by a slat;

a multilayer headbox subdivided at least substantially symmetrically into two channels by a slat that extends outward beyond a nozzle in a region of an outlet gap;

a multilayer headbox equipped with sectional dilution water regulation over a machine width; and

a multilayer headbox equipped with sectional dilution water control over a machine width.

251. (Previously Presented) The device of claim 224, wherein the tissue web is formed with one of:

at least two layers utilizing sectional dilution water regulation and/or control in the headbox; and

at least one layer utilizing sectional dilution water regulation and/or control in the headbox, whereby the at least one layer faces a forming roll.

252. (Previously Presented) The device of claim 224, wherein the tissue web is subjected to greater drying by a drying hood than the at least one drying cylinder.

253. (Previously Presented) The device of claim 252, wherein a ratio of the proportion of the drying by the drying hood and the proportion of the drying with the at least one drying cylinder is one of:

greater than 55:45;

greater than or equal to 60:30;

greater than or equal to 65:35; and

greater than or equal to 70:30.

{P28845 00768603.DOC}

P28845.A10

254. (Previously Presented) The device of claim 224, further comprising a drying hood operating one of:

- at a temperature that is greater than or equal to 400°C;
- at a temperature that is greater than or equal to 500°C;
- at a temperature that is greater than or equal to 600°C; and
- at a temperature that is greater than or equal to 700°C.

255. (Previously Presented) The device of claim 224, wherein the at least one drying cylinder utilizes a steam pressure in the at least one drying cylinder that is one of:

- less than or equal to 0.7 MPa;
- less than or equal to 0.6 MPa; and
- less than or equal to 0.5 MPa.

256. (Previously Presented) The device of claim 224, further comprising one of:  
the tissue web being moved over a carrier drum of the winding device and then wound up onto a spool of the winding device; and  
the tissue web being moved over a driven carrier drum of the winding device and then wound up onto a driven spool of the winding device.

257. (Previously Presented) The device of claim 256, wherein a line force in a winding nip between the carrier drum and the spool is one of:

- less than or equal to 0.8 kN/m;
- less than or equal to 0.5 kN/m; and
- less than or equal to 0.2 kN/m.

258. (Previously Presented) The device of claim 256, wherein a maximum difference between a circumferential speed of the spool and a circumferential speed of the carrier drum is less than 10%.

{P28845 00768603.DOC}

P28845.A10

259. (Currently Amended) The device of claim 224, further comprising one of:

an arrangement for maintaining the free web draw between the at least one drying cylinder and a carrier drum at a predefinable desired value via a drive assigned to the carrier drum irrespective of a line force produced in a winding nip of formed by the carrier drum;

an arrangement for controlling the free web draw between the at least one drying cylinder and a carrier drum via a drive assigned to the carrier drum irrespective of a line force produced in a winding nip of formed by the carrier drum;

an arrangement for regulating the free web draw between the at least one drying cylinder and a carrier drum via a drive assigned to the carrier drum irrespective of a line force produced in a winding nip of formed by the carrier drum[.];

an arrangement for controlling the free web draw between the at least one drying cylinder and a carrier drum via a drive assigned to the carrier drum as a function of a speed of the carrier drum; and

an arrangement for regulating the free web draw between the at least one drying cylinder and a carrier drum via a drive assigned to the carrier drum as a function of a speed of the carrier drum.

260. (Currently Amended) The device of claim 224, wherein the winding drum is a carrier drum and one of:

the winding device comprises [[a]] the carrier drum mounted in a fixed location and a movable spool;

the winding device comprises [[a]] the carrier drum mounted in a fixed location and a movable spool, whereby movement of the spool compensates for an increase in roll diameter of the spool;

the winding device comprises [[a]] the carrier drum mounted in a fixed location and a movable spool, whereby a line force in [[a]] the winding nip of the winding device is set via the movable spool;

the winding device comprises [[a]] the carrier drum mounted in a fixed location and a movable spool, whereby a line force in [[a]] the winding nip of the winding device and a growth of a diameter of the spool is set and compensated for using a common control loop; and

(P28845 00768603.DOC)



P28845.A10

the winding device comprises ~~[[a]]~~ the carrier drum mounted in a fixed location and a movable spool, whereby a line force in ~~[[a]]~~ the winding nip of the winding device is determined via at least one force sensor.

261. (Currently Amended) The device of claim 224, wherein the winding drum is a carrier drum and the winding device comprises ~~[[a]]~~ the carrier drum and a movable spool, and wherein ~~[[a]]~~ the line force is ~~produced in a winding nip of the winding device which~~ is one of:

less than or equal to 0.5 kN/m; and

less than or equal to 0.2 kN/m.

262. (Currently Amended) The device of claim 224, wherein the winding drum is a carrier drum and the winding device comprises ~~[[a]]~~ the carrier drum and a movable spool, and wherein a displacement of the spool is controlled by measuring one of:

a roll diameter of the spool;

a position of the spool relative to the carrier drum;

a position of the spool utilizing sensors; and

a position of the spool utilizing LVDT (linear variable differential transformer) sensors.

263. (Currently Amended) The device of claim 224, wherein the winding drum is a carrier drum and the winding device comprises ~~[[a]]~~ the carrier drum and a movable spool, and wherein one of:

~~[[a]]~~ the line force in ~~[[a]]~~ the winding nip of the winding device is set and controller and a region of the winding nip is monitored with a CCD camera;

~~[[a]]~~ the line force in ~~[[a]]~~ the winding nip of the winding device is set and controlled and a region of the winding nip is monitored with a CCD camera; and

a CCD camera registers a distance between the carrier drum and the spool.

264. (Previously Presented) The device of claim 224, wherein the tissue web has a mass per unit area in an uncreped state that is in the range of between about 11 g/m<sup>2</sup> to about 20 g/m<sup>2</sup> and in a

{P28845 00768603.DOC}

P28845.A10

creped state is in the range of between about 14 g/m<sup>2</sup> to about 24 g/m<sup>2</sup>.

265. (Previously Presented) The device of claim 224, further comprising one of:

a Crescent formed for forming the tissue web, wherein the tissue web is moved with a felt over the Crescent former and then over at least one evacuated device, and thereafter moved through a press nip formed by the at least one drying cylinder;

a Crescent former for forming the tissue web, wherein the tissue web is moved with a felt over the Crescent former and then over a suction roll, and thereafter through a press nip formed by the at least one drying cylinder; and

a Crescent former and a felt for forming the tissue web, wherein the tissue web is move from the Crescent former to an evacuation device, and thereafter through a press nip formed by the at least one drying cylinder.

266. (Previously Presented) The device of claim 224, further comprising a shoe press arranged at the at least one drying cylinder, wherein the shoe press has a shoe length measured in a web running direction that is one of:

greater than or equal to 80 mm; and

greater than or equal to 120 mm.

267. (Previously Presented) The device of claim 224, further comprising a shoe press arranged at the at least one drying cylinder and one of:

a line force being produced in the shoe press which is in the range of between about 60 kN/m to about 90 kN/m;

a maximum pressing pressure being produced in the shoe press that is less than or equal to 2 bar; and

a maximum pressing pressure being produced in the shoe press that is less than or equal to 1.5 bar.

P28845.A10

268. (Previously Presented) The device of claim 224, further comprising a shoe press arranged at the at least one drying cylinder, wherein the shoe press comprises a shoe press unit having a blind-drilled press shell.

269. (Previously Presented) The device of claim 224, wherein the at least one drying cylinder comprises one of:

- a Yankee cylinder; and
- a Yankee cylinder with reinforcing ribs in an interior thereof.

270. (Previously Presented) The device of claim 224, wherein the creping doctor comprises a thickness that is less than or equal to 0.9 mm.

271. (Previously Presented) The device of claim 224, wherein an angle of attack between a tangent of the at least one drying cylinder and the creping doctor is less than or equal to 20°.

272. (Previously Presented) The device of claim 224, wherein a rake angle ( $\beta$ ) of the creping doctor is greater than or equal to 15°.

273. (Currently Amended) The device of claim 224, further comprising one of:  
a device for compensating automatically for a growth of a roll diameter of a spool of the winding device; and

a device for automatically setting [[a]] the line force in [[a]] the winding nip of the winding device.

274. (Currently Amended) A device for producing a tissue web comprising:

- at least one drying cylinder;
- a creping doctor arranged on the at least one drying cylinder;
- a winding device for winding up the tissue web;
- a transfer belt at least largely bridging an entire distance between the creping doctor and the

{P28845 00768603.DOC}

13

**THIS PAGE BLANK (USPTO)**